

AD-A034 001

WOODS HOLE OCEANOGRAPHIC INSTITUTION MASS

F/6 8/3

A COMPILATION OF MOORED CURRENT DATA AND ASSOCIATED OCEANOGRAPH--ETC(U)

MAY 76 S A TARBELL

N00014-66-C-0241


UNCLASSIFIED

WHOI-76-41

NL

1 OF 2
AD
A034001





ADAU34001

UNCLASSIFIED MAY 1976

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER WHOI-76-41	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A COMPILATION OF MOORED CURRENT DATA AND ASSOCIATED OCEANOGRAPHIC OBSERVATIONS, VOLUME XI (LATE 1969 MEASUREMENTS)		5. DATE OF REPORT & PERIOD COVERED TECHNICAL Rept.
6. AUTHOR(s) Susan A. Tarbell		7. CONTRACT OR GRANT NUMBER(s) N00014-66-C-0241 N00014-76-C-0197
8. PERFORMING ORGANIZATION NAME AND ADDRESS Woods Hole Oceanographic Institution Woods Hole, Massachusetts 02543		9. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 083-004 NR 083-400
10. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Code 480		11. DATE May 76
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 150
		14. SECURITY CLASS. (of this report) UNCLASSIFIED
15. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		16. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) 1. Site D 2. Current Data 3. Moorings		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Summaries of wind and current measurements from moored stations gathered by magnetic tape recording current meters and wind recorders, in late 1969 are presented also selected hydrostation data from the same areas. Averaged wind and current quantities are presented in computer generated output as basic STATISTICS, SPECTRA diagrams, PROGRESSIVE VECTOR diagrams and EAST-NORTH component plots. The hydrostation data are presented as temperature and salinity values plotted against pressure.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601UNCLASSIFIED MAY 1976
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

4031 858
WHOI 76-40
DDC
RECEIVED
JAN 8 1976
C

381 000
bpg

WHOI-76-41

A COMPILATION OF MOORED CURRENT DATA AND
ASSOCIATED OCEANOGRAPHIC OBSERVATIONS,
VOLUME XI (LATE 1969 MEASUREMENTS)

by

Susan A. Tarbell

WOODS HOLE OCEANOGRAPHIC INSTITUTION
Woods Hole, Massachusetts 02543

May 1976


TECHNICAL REPORT

*Prepared for the Office of Naval Research under
Contracts N00014-66-C-0241; NR 083-004 and
N00014-76-C-0197; NR 083-400.*

*Reproduction in whole or in part is permitted
for any purpose of the United States Government.
In citing this manuscript in a bibliography, the
reference should be followed by the phrase:
UNPUBLISHED MANUSCRIPT.*

Approved for public release; distribution unlimited.

Approved for Distribution:


Valentine Worthington, Chairman
Department of Physical Oceanography

ABSTRACT

Summaries of wind and current observations from moored stations gathered in late 1969 by magnetic tape recording current meters and wind recorders are presented, also selected hydrostation data from the same areas.

Averaged wind and current variables are presented in computer generated output as basic STATISTICS, SPECTRA diagrams, PROGRESSIVE VECTOR diagrams and EAST-NORTH component plots. The hydrostation data are presented as temperature and salinity values plotted against depth.

ACQUISITION TW	
NTIS	Wallo Section <input checked="" type="checkbox"/>
DOC	Self Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist. Avail. Ext. or SP. DIA.	
A	

TABLE OF CONTENTS

	Page
PREFACE	v
ACKNOWLEDGMENTS	vi
Data Location	vii
Hydrocast Data Selection	x
Current Meter Data Selection	x
Clock	xiv
Back Up Clock Information	xiv
SHEAR TIME	xv
Data Editing	xv
Data Presentation	xvi
Mooring Summary	xvi
Data Summary	xvii
Computer Programs	xvii
Mooring 301	1
3011	3
3014	7
Mooring 302	11
3021	13
Mooring 304	17
3041	19
Mooring 305	23
3051	25
Mooring 309	29
3091	31
3093	35
3095	39
3096	43
Mooring 310	47
3101	49
3102	53
3103	57
3104	61

TABLE OF CONTENTS (cont.)

	Page
Mooring 311	65
3116	67
Mooring 314	71
3141	73
3143	77
Mooring 317	81
3171	83
3173	87
3174	91
3175	95
3176	99
Mooring 318	103
3181	105
Hydrographic Data	110
References	128

PREFACE

This volume is the eleventh of a series of Data Reports intended to present, in summarized form, measurements collected from moored ocean stations. The following is a list of preceding reports.

Volume 1 - Webster and Fofonoff	Data from mid 1963
Volume 2 - Webster and Fofonoff	Data from XII-'63 to V-'64
Volume 3 - Webster and Fofonoff	Data from mid 1964
Volume 4 - Pollard	Data collected in 1965
Volume 5 - Tarbell and Webster	Data collected in 1966
Volume 6 - Tarbell	Data collected in 1967
Volume 7 - Chausse and Tarbell	Data collected in 1968
Volume 8 - Pollard and Tarbell	Array data from 1970
Volume 9 - Tarbell, Briscoe and Chausse	IWEX data from 1973
Volume 10- Tarbell	Data collected in early 1969

The back-up recovery system designed in 1968 (Berteaux and Heinmiller, 1969, W.H.O.I. Ref. 69-7 (unpublished manuscript)) proved its worth in 1969. Tests of wire samples and wire in moorings were continued in 1969. The Gulf Stream went through Site D in April resulting in fish bite damage and a re-evaluation of mooring lines and anchor weights. A change from mechanical clocks to crystal clocks was started at the end of the year.

ACKNOWLEDGMENTS

Unfortunately it is impossible to acknowledge individually everyone who gave support to the Moored Buoy Program in any given year. Ideas from any source are valuable to a growing project and of course the skills of the project support personnel are invaluable. As the Project expanded, more people became involved and specialization started to divide the group into segments. The basic groups became oriented around Instrumentation, Engineering, Operations, Data Processing and of course, the glue that holds us all together, Science.

The instrumentation group became responsible not only for maintaining the instruments but also for improving them and designing equipment to test them for the various malfunctions seen in the lab and in the data.

The engineers design and test new mooring configurations and components to meet more demanding scientific needs.

The operations personnel are also the sea-going personnel. They set and retrieve the moorings and maintain all the equipment necessary for these operations as well as the individual mooring components.

The data processors decode the data and edit out known problems, then arrange the data into forms used by the scientists to interpret the data.

The scientists devise the experiments that the Buoy Group handles and evaluate the returning data.

It is the splendid cooperation among these groups that makes the Buoy Group successful and this Data Report necessary.

The patience and skill of Audrey Williams, who typed the text and tables for this report and of Ann Whitlatch, who prepared the computer plots, is greatly appreciated.

Data Location

The data collected in 1969 were gathered from four different sites: the Mediterranean Sea, the Gulf Stream, Site L and Site D. Mooring 289 was set in the Mediterranean at $38^{\circ} 01'N$, $04^{\circ} 59.9'E$; moorings 304 and 305 were Gulf Stream moorings at $36^{\circ} 23.4'N$, $70^{\circ} 00.2'W$ and $36^{\circ} 43'N$, $70^{\circ} 00.3'W$ respectively. Mooring 314 was set at Site L at $34^{\circ} 02.7'N$, $70^{\circ} 02'W$. The rest of the data were collected from moorings set in the vicinity of Site D, $39^{\circ} 10'N$, $70^{\circ} 00'W$. See figures 1 and 2 for positions of the moorings relative to land.

This report presents data from the later part of 1969. For data from early 1969 see W.H.O.I. Ref. 76-40 (unpublished manuscript).




Figure 1 Mooring Sites in N.W. Atlantic




Figure 2 Mooring Site in Mediterranean Sea

Hydrocast Data Selection

Graphs of temperature and salinity values from Nansen bottle readings are presented at the end of the directional data. The hydrographic stations were selected if they were taken within two days of the mooring period in the vicinity. Figure 3A indicates the relative position in time and depth of the hydrocast data.

Current Meter Data Selection

There were 72 instruments set on 35 moorings by the Buoy Group during 1969. Sixty-four of the instruments were Geodyne model 850 current meter and 8 were current meters modified by Woods Hole to measure wind speed and direction.

A data series was chosen if the quality of the data was good enough to permit basic scientific analysis. Thirty-six current records and five wind records met these requirements. Of the rejected data series, 12 were too short to be included; another 11 had various kinds of electronic failures ranging from writing blank tape for one bits to instrument switching from interval to continuous recording mode; 1 instrument flooded because of a pinched 'O' ring and 7 instruments were not recovered and are considered lost.


A TIME vs. DEPTH graphic presentation of the selected 41 data records is shown in figure 3B.

Data that were initiated between January 1 and May 31 are presented in the preceding report, W.H.O.I. Ref. 76-40 (unpublished manuscript). The remainder of the 1969 data are presented in this report.

SITE 'D' 39°10'N 70°00'W

1969


JAN. + FEB. + MARCH + APRIL + MAY + JUNE + JULY + AUG. + SEPT. + OCT. + NOV. + DEC. +



NON-SITE 'D'

1969

JAN. + FEB. + MARCH + APRIL + MAY + JUNE + JULY + AUG. + SEPT. + OCT. + NOV. + DEC. +



W.H.O.I. Ref. 76-40


W.H.O.I. Ref. 76-41

Figure 3A Selected Hydro Stations Collected near Mooring and Plotted According to Date and Sensor Depth

SITE 'D' 39°10'N 70°00'W

1969

JAN. + FEB. + MARCH + APRIL + MAY + JUNE + JULY + AUG. + SEPT. + OCT. + NOV. + DEC. +




DEPTH IN METERS

x111

NON-SITE 'D'

1969

JAN. + FEB. + MARCH + APRIL + MAY + JUNE + JULY + AUG. + SEPT. + OCT. + NOV. + DEC. +



28°01.0'N, 04°59.9'E
THE MEDITERRANEAN

36°23.4'N 36°43.0'N 34°02.7'N
70°00.2'W 70°00.3'W 70°02.0'W
SITE 'L'
GULF STREAM

W.H.O.I. Ref. 76-40

W.H.O.I. Ref. 76-41

Figure 3B Wind and Current Meter Data Duration Plotted According to Time and Sensor Depth

Clock

During early 1969 the model 850 current meters used two mechanical clocks which were wound up every two minutes by a solenoid, similar to an automobile clock. One of these clocks made 1-hour measurements and the other made 12-hour measurements. The 1-hour clock had a 4 lobe cam on the one-hour shaft which actuated a switch to turn on the recording sequence every 15 minutes. The second clock had a one lobe cam on the 12-hour shaft which also actuated a switch to insert in the data train, a 4 bit instrument number to identify 12-hour record cycles. It also served to re-arm the stop circuit that operates when the tape foil comes up at the end of the second channel of tape to shut off the instrument. The accuracy of these clocks was ± 10 seconds per day.

Late in 1969 a few instruments were modified replacing the two asynchronous mechanical clocks and one R-C oscillator with a single quartz oscillator.

The crystal clock uses a quartz crystal as the time source. It oscillates at a frequency of 74.5654 kHz which drives a chain of 42 divide-by-2 flip-flops. This makes available output pulses at rates up to once per 2048 hours.

Time is indicated by a 14 bit time word at the beginning of each recording interval. The digital clock also provides clocking pulses to the instrument. The accuracy of the digital clock is ± 1 second per day.

Back-up Clock Information

Another time-related activity, first tried in April, puts artificial events at the beginning and the end of each data record. These events, at known real times, provide a check on the accuracy of the clock and in case of a clock problem provide back-up time information with which the accuracy of the time base can be determined. This has proved to be a very valuable procedure for mechanical clock instruments and has also simplified the task of assigning times to data records.

The procedure to place artificial events on tape is as follows:

- A) The instrument is turned on and allowed to run for at least two recording intervals with its rotor taped so it cannot move causing a zero rotor speed on tape.

- B) During the recording cycles of two succeeding records untape the rotor and spin it to cause a speed spike.
- C) Tape the rotor again until just before launch causing more zero rotor speeds.
- D) Do not turn either the clock or the recording part of the instrument off between events and launching.

The reverse procedure applies to the recovery of instruments.

The time when the instrument started recording and the times of the rotor spins are recorded according to radio time signals from stations WWV or CHU.

This procedure also is useful with digital clock instruments in cases where the oscillator is correct but the clock word is malfunctioning.

SHEAR TIME

A program called SHEAR TIME was devised to establish best estimates of time for continuous 850 C. M. data. First, provisional linear corrections for the large clock drift rates (minutes per day) were applied, then the intervals between clock switch closures were displayed graphically. The time rate could then be adjusted with as many linear rate changes as needed to smooth the variations in the switch closures. SHEAR TIME was only used on continuous 850 current meter data which used mechanical clocks for a time base.

Data Editing

Data from both the old mechanical clock model 850 and the new crystal clock model 850 are recorded on 1/4" magnetic tape. The data were transcribed onto computer compatible 7-track tape using a PDP-5 computer (manufactured by Digital Equipment Co.). The data were then converted to Maltais format (J. Maltais, 1969) on 9-track magnetic tape.

Once the data are on tape in Maltais format, various types of editing can be done such as replacing values that are obviously bad or removing systematic instrumental errors. After the data have been edited they are vector averaged over each recording interval to give one velocity vector per interval. These vectors are listed in terms of speed and direction. The launch and retrieval transients are truncated and any remaining bad points are deleted and replaced by linearly interpolated values. The result is an evenly spaced time series called the best basic vector averaged series which is used as input for all further processing.

To insure that each data series has a unique identifier, a set of informal guidelines has been established. For example, 2981WL900

298 - The first three digits are the mooring number.

1 - The fourth digit indicates the position of the instrument on the mooring counting from the top down.

W - When present "W" signifies a wind recorder, a "Y" would signify that the data has been read by eye.

L - Indicates that some editing has been done. The amount of editing done can usually be inferred by the position of the letter in the alphabet. If no editing has been done the symbol \$ is used.

900 - The averaging interval, 900 seconds. 1H would indicate a 1-hour averaging interval.

Data Presentation

Data from wind and current recording instruments are presented first, followed by a section of selected hydrostation data.

The data from each mooring follow a two-page description of that mooring. The data from each selected series are presented with 1 page of instrument information and 3 pages of data displays.

Mooring Summary

The first page of the mooring summary is a diagram of the mooring. The second page contains general information on the mooring. For more detailed information on the moorings set in 1969 see G. Volkmann, 1970, W.H.O.I. Ref. 70-37 (unpublished manuscript).

The mooring page uses the following:

*	data presented
M.C.M.	magnetic tape recording current meters
M.W.R.	magnetic tape recording wind recorders
Tens.	tensiometer
Tel. Tens.	telemetering tensiometer
D.R.	depth recorder
Temp.	temperature recorder
Volt. Dig.	voltage digitizer
Vib/Ten	tensiometer with accelerometer added to measure vibration
Press. Rec.	pressure recorder

Data Summary

The first page of the data summary lists the main features of the data series collected from that instrument. The type of instrument, the sampling scheme, and the timing of the sampling are listed as are the start and stop times of the useable data. All times are Greenwich Mean Time. If the instrument did not work properly, comments on its behavior and the data quality are written under the comments section. Some standard statistical parameters are calculated for the data and are presented on the bottom of the first page. The formulas used to calculate the statistical parameters and descriptions of the various plots used to present the data on the following three pages are described below.

Histograms

Histograms of speed are plotted. The plots may be thought of as approximations to the probability density functions. The vertical axis labeled "relative frequency per unit cell width" shows the percentage of the total record that occurred within a given interval of the horizontal axis. The area under the curve equals 100%.

Statistics (STATS)

Standard statistical parameters are calculated for data in the time range given at the bottom of the table. If there are n speed and direction values in a sample, and we define $E_i = s_i \sin \theta_i$, $N_i = s_i \cos \theta_i$, then for $A = E, N$, and s ,

$$\text{mean, } \bar{A} = \frac{1}{n} \sum_{i=1}^n A_i$$

$$\text{variance, } \sigma_A^2 = \frac{1}{n} \sum_{i=1}^n A_i^2 - \bar{A}^2$$

$$\text{standard error of the mean} = \frac{\sigma_A}{\sqrt{n}}$$

$$\text{standard deviation} = \sigma_A$$

$$\text{skewness} = \frac{1}{\sigma_A^3} \left[\frac{1}{n} \sum_{i=1}^n A_i^3 - \frac{3\bar{A}}{n} \sum_{i=1}^n A_i^2 + 2\bar{A}^3 \right]$$

$$\text{kurtosis} = \frac{1}{\sigma_A^4} \left[\frac{1}{n} \sum_{i=1}^n A_i^4 - \frac{4\bar{A}}{n} \sum_{i=1}^n A_i^3 + \frac{6\bar{A}^2}{n} \sum_{i=1}^n A_i^2 - 3\bar{A}^4 \right]$$

The program also computes "East and North" statistics,

$$\text{covariance, } M = \frac{1}{n} \sum_{i=1}^n E_i N_i - \bar{E} \bar{N}$$

$$\text{standard deviation of covariance, } \sigma_m = \frac{1}{n} \sum_{i=1}^n (E_i N_i)^2 - \overline{E_i N_i}^2$$

$$\text{standard error of covariance} = \frac{\sigma_m}{\sqrt{n}}$$

$$\text{correlation coefficient, } M' = \frac{M}{\sigma_E \sigma_N}$$

STATS also computes these parameters related to vector quantities:

the scalar amplitude of the vector mean, $v_m = \sqrt{\bar{E}^2 + \bar{N}^2}$; vector variance,

$$v_v^2 = \frac{1}{2} (\sigma_E^2 + \sigma_N^2); \text{ standard deviation} = v_v.$$

East vs. North Scatterplot

The EAST and NORTH components are plotted against each other to give a pictorial indication of the DIRECTION and SPEED of the velocity vectors. This type plot can be helpful in finding instrument malfunctions and characteristics not easily noticed elsewhere.

Progressive Vector Diagram (PROVEC)

The EAST and NORTH progressive displacements are computed from the SPEED and DIRECTION values of one recording cycle. The plot begins with

an asterisk (*) on a day boundary. All following day boundaries are indicated with a (+). This type of plot accentuates very low frequency events at the expense of higher frequency oscillations which may be hidden by a large amplitude low-frequency current.

Variable vs. Time Plot

This is a diagram of EAST and NORTH components plotted as a function of TIME. The plot is generated from the basic vector averaged series. This type of plot is complementary to the PROGRESSIVE VECTOR diagram since it accentuates higher frequency events such as inertial and tidal oscillations.

Spectra

The program TIMSAN (Time Series Analysis) uses the Fast Fourier Transform algorithm of Singleton (1969) and is restricted to data segments of length N points, where N must contain no prime factor larger than 5, and must be less than 8000 points; data series longer than this must be broken into two or more pieces.

The number of degrees of freedom for the first 40 plotted points is given by $v = a m s$ where m is the number of adjacent frequency bands being averaged as stated in the label, s is the number of independent data pieces being averaged, again as stated in the label, and a should be two for temperature spectra and for Horizontal Kinetic [HKE] spectra for which the EAST and NORTH components seem statistically independent. In the absence of information regarding NORTH-EAST correlation, one should use $a = 2$ to be safe.

The log-log plot is further averaged during plotting so that more and more points are averaged together as frequency increases. This eliminates the bunching together of points at high frequencies, increases the degrees of freedom of the high frequency estimates, and still permits low-frequency resolution. The averaging algorithm is as follows: counting from the left of the plot, the first 40 plotted points represent data that has been averaged as stated in the label; the data for the next 15 plotted points has been averaged over twice as many frequency bands;

the next 6 over five times as many, the next 40 over ten times as many, the next 15 over twenty times as many, the next 6 over fifty times as many, the next 40 over 100 times as many and so on. In this way, for example, 7900 data points with no averaging indicated in the label would be plotted as only 176 points, and the last 14 estimates would be averaged over 200 basic frequency bands. The m in the formula $\nu = a m s$ for degrees of freedom is, in this example, 200 times larger at the highest frequencies than at the lowest frequencies.


For $\nu > 30$, the confidence limits for the spectral estimates are given approximately by $(1 - 2/9\nu \pm Z\sqrt{2/9\nu})^{1/3}$ where $Z = 1.28375$ for 80% confidence limits, $Z = 1.645$ for 90%, $Z = 1.96$ for 95% and $Z = 2.5757$ for 99%. In the example above, if the HKE spectral plot label had indicated 2 pieces and averaging over 8 adjacent frequency bands then $\nu = 2 \times 2 \times 8 = 32$ for the lowest 40 frequencies (assuming NORTH and EAST components are highly correlated) and $200 \times 32 = 6400$ for the highest frequencies. The 95% confidence intervals (i.e., 95% of the time one would expect the spectral estimates to vary no more than this much) would be (0.57, 1.55) at low frequencies, and (0.97, 1.03) at high frequencies.

For $\nu \leq 30$, one must obtain confidence intervals from Chi-Squared distribution tables in standard statistical references.

1/4" 1 x 19 GAC

STATION 301

5/8" NYLON



LIGHT
RADIO
WIND RECORDER - 30/1

TENSION CELL
TENSIONMETER - 30/2

SWIVEL
10 m CHAIN

TENSION/VIBRATION RECORDER - 30/3

CURRENT METER - 30/4

500 m

CURRENT METER - 30/5

TENSION/VIBRATION RECORDER - 30/6

REMOTE SENSOR

500 m

500 m

549 m

30 m

5 m

361 m

85 m 5/8" NYLON WITH 30 GLASS
SPHERES SPACED 2 m APART

ACOUSTIC BEACON

5 m

ACOUSTIC RELEASE, ORE

15 m

5 m

4750 STIMSON

Mooring No. 301

Set 69 June 07
Year Month Day

39° 09.9N
Latitude

69° 56.0W
Longitude

Set by J. Gifford

Ship R. V. Chain

Cruise 92

Retrieved 69 June 11
Year Month Day

Retrieved by J. Gifford

Ship R. V. Chain

Cruise 92

Purpose of Mooring: Instrumentation test

Mooring Type: Surface mooring - toroid

<u>Data</u> <u>Number</u>	<u>Instrument</u> <u>Number</u>	<u>Type</u>	<u>Depth</u> <u>Meters</u>	<u>Comments</u>
3011*	W-169X	M.W.R.	0	
3012	2001	Tens.	2	
3013	2	Vib/Ten	13	
3014*	M-198	M.C.M.	16	
3015	M-212	M.C.M.	517	No data, electronic problems
3016	3	Vib/Ten	518	

Water depth

2680

COMMENTS ON MOORING:

Data number 3011

Instrument No.: W-169X

Type: Magnetic tape wind recorder

Depth: 0 m

Water depth: 2680 m

Start time: 69-VI-07 121735

Stop time: 69-VI-11 171735

Duration: 4d 5h

Sampling scheme: Continuous

one reading every 5 seconds

COMMENTS:

Wind direction follows ocean current conventions to facilitate comparisons; add 180° to direction for meteorological reading.

STATS

	EAST	NORTH
MEAN	-4.80	-24.94
STD. ERR.	.81	1.42
VARIANCE	793.37	2458.67
STD. DEV.	28.17	49.58
KURTOSIS	2.30	2.39
SKEWNESS	-.50	.68

DATA/ 3011NE300

SPEED	=====	EAST & NORTH	=====
57.80	=	COVARIANCE	= 403.50
.67	=	STD. ERR. OF COVARIANCE	= 47.83
543.83	=	STD. DEV. OF COVARIANCE	= 1880.81
23.32	=	CORRELATION COEFFICIENT	= .353
2.31	=	VECTOR MEAN	= 25.38
.34	=	VECTOR VARIANCE	= 1826.02
	=	STD. DEV.	= 40.32


UNITS OF RAW DATA VARIABLES = CM/SEC

SAMPLE SIZE = 1213 POINTS

SPANNING RANGE


FROM 69-VI-07 12.17.35
TO 69-VI-11 17.17.35




DURATION 4 DAYS 5 H 0 M 0 S




AUTO SPECTRUM
3011WE300 EAST COMP
3011WE300 NORTH COMP


69-VI-07 TO 69-VI-11
1 PIECES WITH 600 ESTIMATES
PER PIECE. AVERAGED OVER
2 ADJACENT FREQUENCY BANDS







08
JUN
69



3011WE1H

Data number 3014

Instrument No.: M-198

Type: Magnetic tape current meter

Depth: 16 m

Water depth: 2680 m

Start time: 69-VI-07 165200

Stop time: 69-VI-11 172200

Duration: 4d 0h 30m

Sampling scheme: Continuous
one reading every 5 seconds

COMMENTS:

STATS

DATA/ 3014C300

MEAN	=	EAST	NORTH	SPEED	=	*****	EAST & NORTH	*****
STD. ERR.	=	-114.97	-224.76	307.46	=	COVARIANCE	=	-4820.66
VARIANCE	=	4.22	4.74	9.71	=	STD. ERR. OF COVARIANCE	=	1190.46
STD. DEV.	=	20869.66	26074.17	16033.71	=	STD. DEV. OF COVARIANCE	=	40620.16
KURTOSIS	=	143.73	181.47	126.23	=	CORRELATION COEFFICIENT	=	-.212
SKEWNESS	=	2.69	2.63	2.43	=	VECTOR MEAN	=	262.45
	=	-.21	.29	-.02	=	VECTOR VARIANCE	=	23366.41
					=	STD. DEV.	=	152.86

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 1160 POINTS

SPANNING RANGE


FROM 69-VI-07 16.52.00


TO 69-VI-11 17.22.00

DURATION 4 DAYS 0 H 30 M 0 S



AUTO SPECTRUM
3014C300 EAST COMP
3014C300 NORTH COMP
16 METERS
69-VI-07 TO 69-VI-11
1 PIECES WITH 576 ESTIMATES
PER PIECE. AVERAGED OVER
2 ADJACENT FREQUENCY BANDS







N
↑

0 30.
KILOMETERS


3014C1H
16 M
69- VI -08 TO 69- VI -11



3014C1H
16 M




08
JUN
69



STATION 302

9/16" NYLON



SYNTACTIC FOAM FLOAT WITH RADIO,
LIGHT AND FLAG

1 m CHAIN

10 m

CURRENT METER - 3021

10 m

ACOUSTIC BEACON

10 m

ACOUSTIC BEACON, AMF

74 m

3 m CHAIN

800 LB. ANCHOR

Mooring No. 302

Set 69 June 07 39° 05.9N 69° 59.5W
Year Month Day Latitude Longitude

Set by J. Gifford Ship R. V. Chain Cruise 92

Retrieved 69 Oct 11
Year Month Day

Retrieved by J. Gifford Ship R. V. Atlantis II Cruise 53

Purpose of Mooring: Long term near-bottom mooring.

Mooring Type: Subsurface mooring with syntactic foam cylinder.

<u>Data Number</u>	<u>Instrument Number</u>	<u>Type</u>	<u>Depth Meters</u>	<u>Comments</u>
3021*	M-159	M.C.M.	2586	

Water depth 2685

Hydrographic Stations

R. V. Chain cruise 92 Station 896

R. V. Chain cruise 92 Station 898

COMMENTS ON MOORING:

Data number 3021

Instrument No.: M-159

Type: Magnetic tape current meter

Depth: 2586 m

Water depth: 2685 m

Start time: 69-VI-08 183305

Stop time: 69-X-11 170305

Duration: 124d 22h 30m

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 16

interval time = 1800 seconds

COMMENTS:

STATS

DATA/ 3021J1000

MEAN	=	EAST	NORTH	SPEED	=	*****	EAST & NORTH	*****
STD. ERR.	=	-22.30	-9.41	66.00	=	COVARIANCE	=	-705.20
VARIANCE	=	.55	.70	.63	=	STD. ERR. OF COVARIANCE	=	45.64
STD. DEV.	=	1700.05	3787.23	1712.12	=	STD. DEV. OF COVARIANCE	=	3620.62
KURTOSIS	=	42.43	61.30	41.30	=	CORRELATION COEFFICIENT	=	-.204
SKEWNESS	=	9.21	9.80	4.45	=	VECTOR MEAN	=	22.63
	=	.10	-.00	1.05	=	VECTOR VARIANCE	=	2783.50
					=	STD. DEV.	=	52.76

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 5000 POINTS

SPANNING RANGE


FROM 69- VI -00 18.33.05



TO 69- X -11 17.03.05

DURATION 124 DAYS 22 H 30 M 0 S



AUTO SPECTRUM
3021J1800 EAST COMP
3021J1800 NORTH COMP
2586 METERS
69-VI-08 TO 69-X-08
1 PIECES WITH 2916 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS







0. 60. KILOMETERS

3021J1H


2586 M

69- VI -09 TO 69- X -11






3021J1H
max 5



STATION 304



GLASS BALL BUOY WITH
RADIO, LIGHT AND FLAG

1 m CHAIN

10 m 9/16" NYLON

10 m SAME

CURRENT METER - 3041

10 m 9/16" NYLON

ACOUSTIC RELEASE, AMF

172 m 9/16" NYLON

12 m SAME

3 m CHAIN

2 400 LB. STIMSON ANCHORS

Mooring No. 304

Set 69 June 12 36° 23.4N 70° 00.2W
Year Month Day Latitude Longitude

Set by J. Gifford Ship R. V. Chain Cruise 92

Retrieved 69 Aug 14
Year Month Day

Retrieved by R. Heinmiller Ship R. V. Chain Cruise 95

Purpose of Mooring: To study current structure under the Gulf Stream.

Mooring Type: Subsurface mooring with glass ball float.

<u>Data</u> <u>Number</u>	<u>Instrument</u> <u>Number</u>	<u>Type</u>	<u>Depth</u> <u>Meters</u>	<u>Comments</u>
3041*	M-122	M.C.M.	4287	

Water depth 4486

COMMENTS ON MOORING:

Data number 3041

Instrument No.: M-122

Type: Magnetic tape current meter

Depth: 4287 m

Water depth: 4486 m

Start time: 69-VI-12 204825

Stop time: 69-VIII-14 034825

Duration: 62d 7h

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 16

interval time = 1800 seconds

COMMENTS:

STATS

	EAST	NORTH
MEAN	44.03	88.42
STD. ERR.	1.60	3.86
VARIANCE	7686.45	46830.23
STD. DEV.	87.67	216.63
KURTOSIS	6.22	2.21
SKEWNESS	-1.45	-.78

DATA/ 3041J1800

	SPEED	EAST & NORTH	
	237.36		COVARIANCE = 11115.98
	1.66		STD. ERR. OF COVARIANCE = 370.76
	8214.13		STD. DEV. OF COVARIANCE = 20276.85
	80.63		CORRELATION COEFFICIENT = .505
	2.17		VECTOR MEAN = 88.67
	-.25		VECTOR VARIANCE = 27308.94
			STD. DEV. = 165.25


UNITS OF RAW DATA VARIABLES = MM/SEC

SAMPLE SIZE = 2881 POINTS


SPANNING RANGE




FROM 69-VI-12 20.48.25
TO 69-VIII-14 03.48.25


DURATION 62 DAYS 7 H 0 M 0 S



AUTO SPECTRUM
3041J1800 EAST COMP
3041J1800 NORTH COMP
4287 METERS
69-VI-12 TO 69-VIII-12
1 PIECES WITH 1458 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS







30N1J1H
1000 1500/1000 1000

2 400 LB STIMSON ANCHORS

Mooring No. 305

Set 69 June 12 36° 43.0N 70° 00.3W
Year Month Day Latitude Longitude

Set by J. Gifford Ship R. V. Chain Cruise 92

Retrieved 69 Aug 14
Year Month Day

Retrieved by R. Heinmiller Ship R. V. Chain Cruise 95

Purpose of Mooring: To study current structure under the Gulf Stream.

Mooring Type: Subsurface mooring with glass ball float.

<u>Data</u> <u>Number</u>	<u>Instrument</u> <u>Number</u>	<u>Type</u>	<u>Depth</u> <u>Meters</u>	<u>Comments</u>
3051*	M-127	M.C.M.	4227	

Water depth 4426

COMMENTS ON MOORING:

Data number 3051

Instrument No.: M-127

Type: Magnetic tape current meter

Depth: 4227 m

Water depth: 4426 m

Start time: 69-VI-12 183355

Stop time: 69-VIII-14 093355

Duration: 62d 15h

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 16

interval time = 1800 seconds

COMMENTS:

STATS

DATA/ 305101800

MEAN	"	EAST	NORTH	SPEED	"	####	EAST & NORTH	####
STD. ERR.	"	22.86	103.80	239.56	"	COVARIANCE	"	10206.47
VARIANCE	"	1.74	3.87	1.81	"	STD. ERR. OF COVARIANCE	"	344.38
STD. DEV.	"	8076.88	45087.72	10847.58	"	STD. DEV. OF COVARIANCE	"	18884.48
KURTOSIS	"	85.27	212.36	104.63	"	CORRELATION COEFFICIENT	"	.504
SKEWNESS	"	6.08	2.51	2.14	"	VECTOR MEAN	"	108.41
	"	-1.53	-.85	.18	"	VECTOR VARIANCE	"	27087.30
					"	STD. DEV.	"	164.58

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 3007 POINTS

SPANNING RANGE


FROM 69-VI-12 18.33.55




TO 69-VIII-14 09.33.55

DURATION 62 DAYS 15 H 0 M 0 S




AUTO SPECTRUM
3051D1800 EAST COMP
3051D1800 NORTH COMP
4227 METERS
69-VI-12 TO 69-VIII-14
1 PIECES WITH 1500 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS






1400 1200/100 1400



1400 1200/100 1400



305101H
1000 0

STATION 309

ALL LINE 9/16" PLAID NYLON

65 LB DANFORTH WITH
3 m CHAIN

LIGHT
RADIO
WIND RECORDER - 3091

TELEMETERING TENSIO METER - 3092
10 m CHAIN

CURRENT METER - 3093

TENSIO METER - 3094

40 m

CURRENT METER - 3095

50 m

CURRENT METER - 3096

400 m

500 m

TEMPERATURE RECORDER - 3097

500 m

CURRENT METER - 3098

500 m

282 m

TENSIO METER - 3099

85 m 9/16" NYLON WITH 20 GLASS
BALLS SPACED 2 m APART

ACOUSTIC BEACON

15 m

TIMED RELEASE, GEODYNE

5 m

5 m CHAIN

5100 LB. STIMSON ANCHOR

Mooring No. 309

Set 69 June 13 39° 09.0N 70° 00.2W
 Year Month Day Latitude Longitude

Set by J. Gifford Ship R. V. Chain Cruise 92

Retrieved 69 Aug 11
 Year Month Day

Retrieved by R. Heinmiller Ship R. V. Chain Cruise 95

Purpose of Mooring: Long term current measurements at Site D.

Mooring Type: All nylon surface mooring.

<u>Data Number</u>	<u>Instrument Number</u>	<u>Type</u>	<u>Depth Meters</u>	<u>Comments</u>
3091*	W-101X	M.W.R.	0	
3092	2001	Tel. Tens.	2	
3093*	M-203	M.C.M.	13	
3094	1023	Tens.	14	
3095*	M-214	M.C.M.	56	
3096*	M-213	M.C.M.	108	
3097	T-452	Temp.	1000	Lost
3098	M-211	M.C.M.	1692	Lost
3099	1024	Tens.	2565	Lost

Water depth 2678

Hydrographic Station

R. V. Chain cruise 92 Station 896

R. V. Chain cruise 92 Station 903

R. V. Chain cruise 95 Station 922

COMMENTS ON MOORING:

Surface toroid seen on July 6, 1969 by U.S.S. WALDO COUNTY. The mooring was hauled on August 11 because of hurricane threat. During recovery the line parted around 500 meters down the mooring. The release timer should have fired on August 12 1200. On August 29 the beacon was indicating it was still on station.

Data number 3091

Instrument No.: W-101X

Type: Magnetic tape wind recorder

Depth: -0-

Water depth: 2678 m

Start time: 69-VI-13 203640

Stop time: 69-VIII-11 210640

Duration: 59d 0h 30m

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 24

interval time = 1800 seconds

COMMENTS:

Wind direction follows ocean current conventions to facilitate comparisons; add 180° to direction for meteorological reading.

STATS

DATA/ 3091WH800

MEAN	=	EAST	NORTH	SPEED	=	#####	EAST & NORTH	#####
STD. ERR.	=	8.89	11.78	49.50	=	COVARIANCE	=	417.81
VARIANCE	=	.43	.51	.23	=	STD. ERR. OF COVARIANCE	=	15.27
STD. DEV.	=	1048.28	1487.19	305.07	=	STD. DEV. OF COVARIANCE	=	1149.57
KURTOSIS	=	32.38	38.58	17.47	=	CORRELATION COEFFICIENT	=	.335
SKEWNESS	=	2.89	1.87	3.31	=	VECTOR MEAN	=	14.82
	=	-.30	-.31	.25	=	VECTOR VARIANCE	=	1287.79
					=	STD. DEV.	=	35.61


UNITS OF RAW DATA VARIABLES = CM/SEC

SAMPLE SIZE = 5867 POINTS


SPANNING RANGE



FROM 69-VI-13 20.36.40
TO 69-VIII-11 21.06.40

DURATION 59 DAYS 0 H 30 M 0 S



AUTO SPECTRUM
3091WH900 EAST COMP
3091WH900 NORTH COMP
69-VI-13 TO 69-VIII-09
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS





Data number 3093

Instrument No.: M-203

Type: Tape recording current meter

Depth: 13 m

Water depth: 2678 m

Start time: 69-VI-13 205235

Stop time: 69-VIII-11 212235

Duration: 59d 0h 30m

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

STATS

DATA/ 30930900

MEAN	=	EAST	NORTH	SPEED	=	####	EAST & NORTH	####
STD. ERR.	=	.55	88.80	287.84	=	COVARIANCE	=	-3888.04
VARIANCE	=	3.02	2.84	1.71	=	STD. ERR. OF COVARIANCE	=	609.23
STD. DEV.	=	51880.00	45580.88	18587.00	=	STD. DEV. OF COVARIANCE	=	45882.85
KURTOSIS	=	227.95	219.45	128.71	=	CORRELATION COEFFICIENT	=	-.080
SKEWNESS	=	2.82	2.87	2.48	=	VECTOR MEAN	=	88.80
	=	-.02	-.57	.05	=	VECTOR VARIANCE	=	48825.94
					=	STD. DEV.	=	220.51

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 5667 POINTS

SPANNING RANGE


FROM 69-VI-13 20.52.35


TO 69-VIII-11 21.22.35

DURATION 59 DAYS 0 H 30 M 0 S




AUTO SPECTRUM
3093D900 EAST COMP
3093D900 NORTH COMP
13 METERS
69-VI-13 TO 69-VIII-09
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS





69- VI -14 TO 69-VIII-11



Data number 3095

Instrument No.: M-214

Type: Magnetic tape current meter

Depth: 56 m

Water depth: 2678 m

Start time: 69-VI-13 212025

Stop time: 69-VIII-11 213525

Duration: 59d 0h 15m

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

STATS

DATA/ 3095E800

MEAN	EAST	NORTH	SPEED	EAST & NORTH	
STD. ERR.	-21.02	1.02	130.01	COVARIANCE	-3424.17
VARIANCE	1.68	1.10	.84	STD. ERR. OF COVARIANCE	145.68
STD. DEV.	16086.38	8008.10	4007.95	STD. DEV. OF COVARIANCE	10865.84
KURTOSIS	128.83	88.48	70.83	CORRELATION COEFFICIENT	-.302
SKEWNESS	2.52	3.03	3.30	VECTOR MEAN	21.05
	-.03	-.44	.55	VECTOR VARIANCE	12048.23
				STD. DEV.	109.76

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 5668 POINTS

SPANNING RANGE


FROM 69-VI-13 21.20.25


TO 69-VIII-11 21.35.25


DURATION 59 DAYS 0 H 15 M 0 S



AUTO SPECTRUM
3095E900 EAST COMP
3095E900 NORTH COMP
56 METERS
69-VI-13 TO 69-VIII-09
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS







Data number 3096

Instrument No.: M-213

Type: Magnetic tape current meter

Depth: 108 m

Water depth: 2678 m

Start time: 69-VI-13 210850

Stop time: 69-VIII-11 210850

Duration: 59d

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

STATS

DATA/ 3086C900

MEAN	EAST	NORTH	SPEED	=====	EAST & NORTH	=====
STD. ERR.	-11.21	-1.17	123.03	= COVARIANCE	=	-3058.57
VARIANCE	1.48	1.02	.71	= STD. ERR. OF COVARIANCE	=	107.01
STD. DEV.	12007.73	5086.34	2002.44	= STD. DEV. OF COVARIANCE	=	8054.28
KURTOSIS	100.50	78.72	53.00	= CORRELATION COEFFICIENT	=	-.384
SKEWNESS	2.04	9.34	2.03	= VECTOR MEAN	=	11.21
	.42	-.78	.37	= VECTOR VARIANCE	=	8840.53
				= STD. DEV.	=	94.59

UNITS OF RAW DATA VARIABLES = CM/SEC


SAMPLE SIZE = 5086 POINTS

SPANNING RANGE

FROM 69-VI-13 21.00.00


TO 69-VIII-11 21.00.00


DURATION 59 DAYS 0 H 0 M 0 S




AUTO SPECTRUM
3096C900 EAST COMP
3096C900 NORTH COMP
108 METERS


69-VI-13 TO 69-VIII-09
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS







STATION 310



Mooring No. 310

Set 69 Aug 11 39° 10.0N 70° 02.5W
Year Month Day Latitude Longitude

Set by R. Heinmiller Ship R. V. Chain Cruise 95

Retrieved 70 Jan 04
Year Month Day

Retrieved by R. Heinmiller Ship R. V. Chain Cruise 97

Purpose of Mooring: Four months current measurements at Site D.

Mooring Type: Subsurface 4 foot sphere.

<u>Data Number</u>	<u>Instrument Number</u>	<u>Type</u>	<u>Depth Meters</u>	<u>Comments</u>
3101*	M-142	M.C.M.	200	
3102*	M-175	M.C.M.	532	
3103*	M-215	M.C.M.	1044	
3104*	M-204	M.C.M.	2066	

Water depth 2683

Hydrographic Stations

R. V. Chain cruise 95 Station 922

COMMENTS ON MOORING:

Data number 3101

Instrument No.: M-142

Type: Magnetic tape current meter

Depth: 200 m

Water depth: 2683 m

Start time: 69-VIII-11 154600

Stop time: 69-IX-15 174600

Duration: 35d 2h

Sampling scheme: Interval

time between strobes = 5.27 seconds

no. of strobes per interval = 24

interval time = 1800 seconds

COMMENTS:

Digital clock - clock lost 1 minute 48 seconds over 5 month period.

Data becomes noisy after a month.

STATS

DATA/ 3101A1800

MEAN	=	EAST	NORTH	SPEED	=	UNKN	EAST & NORTH	UNKN
STD. ERR.	=	4.89	24.57	81.89	=	COVARIANCE	=	2370.48
VARIANCE	=	1.83	1.59	1.28	=	STD. ERR. OF COVARIANCE	=	143.47
STD. DEV.	=	6284.84	4271.87	2741.41	=	STD. DEV. OF COVARIANCE	=	5888.23
KURTOSIS	=	79.28	85.36	52.36	=	CORRELATION COEFFICIENT	=	.457
SKEWNESS	=	3.80	2.65	4.89	=	VECTOR MEAN	=	25.07
		.95	.22	1.24	=	VECTOR VARIANCE	=	5278.40
					=	STD. DEV.	=	72.65

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 1685 POINTS

SPANNING RANGE


FROM 69-VIII-11 15.46.00


TO 69-IX-15 17.46.00



DURATION 35 DAYS 2 H 0 M 0 S



AUTO SPECTRUM
3101A1800 EAST COMP
3101A1800 NORTH COMP
200 METERS
69-VIII-11 TO 69-IX-14
1 PIECES WITH 810 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS







3101A1H
200 M

Data number 3102

Instrument No.: M-175

Type: Magnetic tape current meter

Depth: 532 m

Water depth: 2683 m

Start time: 69-VIII-11 154900

Stop time: 69-X-12 131900

Duration: 61d 21h 30m

Sampling scheme: Interval

time between strobes = 5 seconds
no. of strobes per interval = 24
interval time = 1800 seconds

COMMENTS:

Battery leaked

Channel 'A' data only

Much tape slippage made data hard to read.

STATS

	EAST	NORTH
MEAN	-10.24	-15.44
STD. ERR.	1.13	.80
VARIANCE	3012.80	2375.01
STD. DEV.	61.75	48.73
KURTOSIS	2.73	2.50
SKEWNESS	.42	-.14

DATA/ 310201800

	EAST & NORTH	
SPEED	75.07	COVARIANCE
.61	STD. ERR. OF COVARIANCE	1123.12
33.51	STD. DEV. OF COVARIANCE	3050.62
2.84	CORRELATION COEFFICIENT	-.454
.61	VECTOR MEAN	23.80
	VECTOR VARIANCE	3083.85
	STD. DEV.	55.62


UNITS OF RAW DATA VARIABLES = MM/SEC

SAMPLE SIZE = 2872 POINTS


SPANNING RANGE



FROM 69-VIII-11 15.48.00
TO 69-X-12 13.19.00

DURATION 61 DAYS 21 H 30 M 0 S




AUTO SPECTRUM
3102D1800 EAST COMP
3102D1800 NORTH COMP
532 METERS
69-VIII-11 TO 69-X-11
1 PIECES WITH 1458 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS





0. 60.
KILOMETERS
310201H
532 M
69-VIII-12 TO 69- X -12



Data number 3103

Instrument No.: M-215

Type: Magnetic tape current meter

Depth: 1044 m

Water depth: 2683 m

Start time: 69-VIII-11 182955

Stop time: 69-XII-07 012955

Duration: 117d 7h

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 24

interval time = 1800 seconds

COMMENTS:

STATS

DATA/ 3103C1800

MEAN	EAST	NORTH	SPEED	EAST & NORTH	
-30.88	-17.84	71.12	COVARIANCE	-717.54	
STD. ERR.	.67	.68	.40	STD. ERR. OF COVARIANCE	40.21
VARIANCE	2540.70	2588.74	1327.43	STD. DEV. OF COVARIANCE	3692.86
STD. DEV.	50.41	50.88	36.43	CORRELATION COEFFICIENT	-.281
KURTOSIS	3.10	4.00	6.01	VECTOR MEAN	35.71
SKEWNESS	.30	-.87	1.45	VECTOR VARIANCE	2555.28
			STD. DEV.		50.55

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 5631 POINTS

SPANNING RANGE


FROM 69-VIII-11 18.29.55


TO 69-XII-07 01.29.55

DURATION 117 DAYS 7 H 0 M 0 S



AUTO SPECTRUM
3103C1800 EAST COMP
3103C1800 NORTH COMP
1044 METERS
69-VIII-11 TO 69-XII-02
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS






N


0. 60. KILOMETERS

3103C1H


1044 M

69-VIII-12 TO 69- XII-07





3103C1H
1000



Data number 3104

Instrument No.: M-204

Type: Magnetic tape current meter

Depth: 2066 m

Water depth: 2683 m

Start time: 69-VIII-11 154110

Stop time: 69-XII-08 124110

Duration: 118d 21h

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 24

interval time = 1800 seconds

COMMENTS:

STATS

DATA/ 310401000

MEAN	=	EAST	NORTH	SPEED	=	*****	EAST & NORTH	*****
STD. ERR.	=	-16.73	.07	48.70	=	COVARIANCE	=	-374.70
VARIANCE	=	.48	.48	.28	=	STD. ERR. OF COVARIANCE	=	18.43
STD. DEV.	=	1358.40	1281.37	458.24	=	STD. DEV. OF COVARIANCE	=	1487.88
KURTOSIS	=	36.88	35.84	21.43	=	CORRELATION COEFFICIENT	=	-.283
SKEWNESS	=	2.72	2.55	3.11	=	VECTOR MEAN	=	18.73
		.37	-.01	.72	=	VECTOR VARIANCE	=	1324.88
					=	STD. DEV.	=	36.40

UNITS OF RAW DATA VARIABLES = MM/SEC

SAMPLE SIZE = 5707 POINTS


SPANNING RANGE

FROM 69-VIII-11 15.41.10


TO 69-XII-08 12.41.10

DURATION 118 DAYS 21 H 0 M 0 S

HISTO PLOT
3104D1800
SPEED





AUTO SPECTRUM
3104D1800 EAST COMP
3104D1800 NORTH COMP
2066 METERS
69-VIII-11 TO 69-XII-02
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS





PERIOD, HRS.
100
10

FREQUENCY, CYCLES/HRS.
0.01
0.1




310000H



STATION 311

9/16" NYLON

5/8" NYLON



Mooring No. 311

Set 69 Aug 11 39° 11.2N 70° 04.9W
Year Month Day Latitude Longitude

Set by R. Heinmiller Ship R. V. Chain Cruise 95

Retrieved 69 Oct 06
Year Month Day

Retrieved by J. Gifford Ship R. V. Atlantis II Cruise 53

Purpose of Mooring: Current measurements at Site D.

Mooring Type: Surface mooring - toroid

<u>Data Number</u>	<u>Instrument Number</u>	<u>Type</u>	<u>Depth Meters</u>	<u>Comments</u>
3111	W-119X	M.W.R.	0	Lost
3112	1016	Tens.	3	
3113	T-456	Temp.	3	
3114	M-208	M.C.M.	15	Lost
3115	M-191	M.C.M.	56	Instrument was recording double records
3116*	M-206	M.C.M.	108	
3117	1014	Tens.	109	
3118	M-220	M.C.M.	210	Compass and vane zero after 3 weeks
Water depth			2685	

Hydrographic Station

R. V. Atlantis II cruise 53 Station 1550

COMMENTS ON MOORING:

Mooring recovered using back-up recovery system. Tensiometer reading indicates great strain on mooring September 16, 1969. Top 50 meters of mooring considered stolen.

Data number 3116

Instrument No.: M-206

Type: Magnetic tape current meter

Depth: 108 m

Water depth: 2685 m

Start time: 69-VIII-11 224800

Stop time: 69-IX-17 121800

Duration: 36d 13h 30m

Sampling scheme: Interval

time between strobes = 5 seconds
no. of strobes per interval = 24
interval time = 1800 seconds

COMMENTS:

STATS

DATA/ 3116C1800

MEAN	=	EAST	NORTH	SPEED	=	*****	EAST & NORTH	*****
STD. ERR.	=	12.28	41.24	131.70	=	COVARIANCE	=	4323.51
VARIANCE	=	2.51	2.26	1.62	=	STD. ERR. OF COVARIANCE	=	235.61
STD. DEV.	=	11094.16	9008.57	4008.84	=	STD. DEV. OF COVARIANCE	=	9873.35
KURTOSIS	=	105.33	84.91	67.89	=	CORRELATION COEFFICIENT	=	.432
SKEWNESS	=	2.89	2.48	2.89	=	VECTOR MEAN	=	43.03
		.53	.11	.52	=	VECTOR VARIANCE	=	10051.38
					=	STD. DEV.	=	100.26

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 1756 POINTS

SPANNING RANGE


FROM 69-VIII-11 22.48.00
TO 69-IX-17 12.18.00



DURATION 36 DAYS 13 H 30 M 0 S



HISTO PLOT
3116C1800
SPEED




AUTO SPECTRUM
3116C1800 EAST COMP
3116C1800 NORTH COMP
108 METERS
69-VIII-11 TO 69-IX-16
1 PIECES WITH 864 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS









Mooring No. 314

Set 69 Aug 18 34° 02.7N 70° 02.0W
Year Month Day Latitude Longitude

Set by R. Heinmiller Ship R. V. Chain Cruise 95

Retrieved 69 Oct 8
Year Month Day

Retrieved by J. Gifford Ship R. V. Atlantis II Cruise 53

Purpose of Mooring: Two month wire test at Site L.

Mooring Type: Surface mooring - toroid.

<u>Data</u> <u>Number</u>	<u>Instrument</u> <u>Number</u>	<u>Type</u>	<u>Depth</u> <u>Meters</u>	<u>Comments</u>
3141*	W-169X	M.W.R.	-0-	
3142	1025	Tens	13	
3143*	M-198	M.C.M.	14	
3144	1026	Tens	2015	
3145	1027	Tens	5259	

Water depth 5368

Hydrographic Station

R. V. Chain cruise 95 Station 924

R. V. Atlantis II cruise 53 Station 1551

COMMENTS ON MOORING:

Data number 3141

Instrument No.: W-169X

Type: Magnetic tape wind recorder

Depth: -0-

Water depth: 5368 m

Start time: 69-VIII-18 095950

Stop time: 69-X-09 014450

Duration: 51d 15h 45m

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

Wind direction follows ocean current conventions to facilitate comparisons;
add 180° to direction for meteorological readings.

STATS

DATA/ 3141NF900

	EAST	NORTH
MEAN	-13.86	-14.50
STD. ERR.	.61	.66
VARIANCE	1818.25	2181.72
STD. DEV.	42.62	46.49
KURTOSIS	2.53	2.85
SKEWNESS	.81	.11

SPEED	EAST & NORTH	
61.30	COVARIANCE	409.18
.36	STD. ERR. OF COVARIANCE	30.38
825.19	STD. DEV. OF COVARIANCE	2133.87
25.00	CORRELATION COEFFICIENT	.207
3.88	VECTOR MEAN	20.13
.88	VECTOR VARIANCE	1988.99
	STD. DEV.	44.60

UNITS OF RAW DATA VARIABLES = CM/SEC


SAMPLE SIZE = 4880 POINTS

SPANNING RANGE


FROM 69-VIII-18 09.59.50


TO 69-X-09 01.44.50

DURATION 51 DAYS 15 H 45 M 0 S




AUTO SPECTRUM
3141WF900 EAST COMP
3141WF900 NORTH COMP
69-VIII-18 TO 69-X-08
1 PIECES WITH 2430 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS





N ↑

0. KILOMETERS 1500.
 3141WFIH
 WIND
 69-VIII-19 TO 69- X -09



AD-A034 001 WOODS HOLE OCEANOGRAPHIC INSTITUTION MASS

A COMPILATION OF MOORED CURRENT DATA AND ASSOCIATED OCEANOGRAPH--ETC(U)

GRAPH--ETC(U)


N00014-66-C-0241


NL

2 of 2
AD
A034001

AD
A034001

DATE
FILMED
2-77





Data number 3143

Instrument No.: M-198

Type: Magnetic tape current meter

Depth: 14 m

Water depth: 5368 m

Start time: 69-VIII-18 095353

Stop time: 69-X-09 015353

Duration: 51d 16h

Sampling scheme: Interval

time between strobes = 5 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

STATS

DATA/ 31430800

MEAN	=	EAST	NORTH	SPEED	=	####	EAST & NORTH	####
STD. ERR.	=	55.88	-11.50	104.68	=	COVARIANCE	=	-2568.70
VARIANCE	=	2.12	2.10	1.39	=	STD. ERR. OF COVARIANCE	=	335.61
STD. DEV.	=	22298.47	21871.48	8578.20	=	STD. DEV. OF COVARIANCE	=	23638.45
KURTOSIS	=	148.13	148.23	87.87	=	CORRELATION COEFFICIENT	=	-.118
SKEWNESS	=	9.81	2.55	9.30	=	VECTOR MEAN	=	57.16
	=	-.01	-.18	.55	=	VECTOR VARIANCE	=	22104.88
					=	STD. DEV.	=	148.68

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 4861 POINTS

SPANNING RANGE


FROM 69-VIII-18 09.53.53


TO 69-X-09 01.53.53


DURATION 51 DAYS 16 H 0 M 0 S



AUTO SPECTRUM
31430900 EAST COMP
31430900 NORTH COMP
14 METERS
69-VIII-18 TO 69-X-08
1 PIECES WITH 2430 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS








STATION 317

9/16" NYLON



Mooring No. 317

Set 69 Oct 06 39° 12.0N 70° 02.8W
 Year Month Day Latitude Longitude

Set by J. Gifford Ship R. V. Atlantis II Cruise 53

Retrieved 70 Jan 05
 Year Month Day

Retrieved by R. Heinmiller Ship R. V. Chain Cruise 97

Purpose of Mooring: Horizontal mooring array with moorings no. 318 and 310.

Mooring Type: Surface mooring.

Data Number	Instrument Number	Type	Depth Meters	Comments
3171*	W-101X	M.W.R.	-0-	
3172		Temp	11	
3173*	M-122	M.C.M.	13	
3174*	M-212	M.C.M.	53	
3175*	M-213	M.C.M.	105	
3176*	M-203	M.C.M.	207	
3177	M-129	M.C.M.	1000	Unable to read tape
Water depth			2681	

Hydrographic Stations

R. V. Atlantis II cruise 53 Station 1550

R. V. Atlantis II cruise 53 Station 1552

COMMENTS ON MOORING:

Data number 3171

Instrument No.: W-101X

Type: Magnetic tape wind recorder

Depth: -0-

Water depth: 2681 m

Start time: 69-X-06 145330

Stop time: 69-XII-01 050830

Duration: 55d 14h 15m

Sampling scheme: Interval

time between strobes = 5.27 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

One of the first digital clock records. Near the end of the record the data gets progressively worse then dies before the end of the tape. Wind direction follows ocean current conventions to facilitate comparisons; add 180° to direction for meteorological readings.

STATS

DATA/ 3171WJ800

	EAST	NORTH	SPEED	EAST & NORTH	
MEAN	18.14	-13.41	80.27		251.88
STD. ERR.	.86	.72	.39		43.74
VARIANCE	3841.71	2730.88	774.84		3185.77
STD. DEV.	62.78	52.28	27.84		.077
KURTOSIS	1.85	2.40	2.87		23.97
SKEWNESS	-.15	.18	.24		3338.30
					57.76


UNITS OF RAW DATA VARIABLES = CM/SEC

SAMPLE SIZE = 5938 POINTS

SPANNING RANGE


FROM 69- X -06 14.53.30
TO 69- XII-01 05.08.30


DURATION 55 DAYS 14 H 15 M 0 S



AUTO SPECTRUM
3171WJ900 EAST COMP
3171WJ900 NORTH COMP

69-X-06 TO 69-XI-29
1 PIECES WITH 2592 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS






0 2500
KILOMETERS

3171WJ1H

WIND

69- X -07 TO 69- XII-01



23

20

69-I-07

13

16

25

28

07

05

11

14

17

21


31



69-II-01

25

30

69-XII-01





Data number 3173

Instrument No.: M-122

Type: Magnetic tape current meter

Depth: 13 m

Water depth: 2681 m

Start time: 69-X-06 145330

Stop time: 69-XII-07 033830

Duration: 61d 12h 45m

Sampling scheme: Interval

time between strobes = 5.27 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

Digital clock - 20 seconds too fast over 3 month period. Good record until near end of recording. Battery running down may be cause of bad records at end.

STATS

	EAST	NORTH
MEAN	43.10	-31.22
STD. ERR.	3.67	5.23
VARIANCE	78542.80	161417.88
STD. DEV.	282.03	401.77
KURTOSIS	2.80	1.93
SKEWNESS	.31	-.28

DATA/ 31730900

	EAST & NORTH	
SPEED	444.84	COVARIANCE = 42938.86
2.78		STD. ERR. OF COVARIANCE = 1425.85
45807.83		STD. DEV. OF COVARIANCE = 109580.35
214.26		CORRELATION COEFFICIENT = .378
2.11		VECTOR MEAN = 53.22
.08		VECTOR VARIANCE = 120480.35
		STD. DEV. = 347.10


UNITS OF RAW DATA VARIABLES = MM/SEC

SAMPLE SIZE = 5808 POINTS


SPANNING RANGE



FROM 69- X -06 14.53.30
TO 69- XII-07 03.38.30

DURATION 61 DAYS 12 H 45 M 0 S



AUTO SPECTRUM
31730900 EAST COMP
31730900 NORTH COMP
13 METERS
69-X-06 TO 69-XII-06
1 PIECES WITH 2916 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS






0 200.
KILOMETERS

3173D1H

13 M

69- X -07 TO 69- XII-07



Data number 3174

Instrument No.: M-212

Type: Magnetic tape current meter

Depth: 53 m

Water depth: 2681 m

Start time: 69-X-06 145330

Stop time: 69-XII-04 075330

Duration: 58d 17h

Sampling scheme: Interval

time between strobes = 5.27 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

Digital clock - 16 seconds too fast over 3 month period.

STATS

DATA/ 3174E800

MEAN	=	EAST	NORTH	SPEED	=	MEAN	EAST & NORTH	MEAN
STD. ERR.	=	44.87	-78.43	407.84	=	COVARIANCE	=	41788.88
VARIANCE	=	3.45	4.78	2.80	=	STD. ERR. OF COVARIANCE	=	1167.48
STD. DEV.	=	67285.85	128485.88	38141.53	=	STD. DEV. OF COVARIANCE	=	63148.23
KURTOSIS	=	288.24	358.88	185.30	=	CORRELATION COEFFICIENT	=	.447
SKEWNESS	=	2.43	1.74	1.84	=	VECTOR MEAN	=	88.63
	=	.38	-.31	-.07	=	VECTOR VARIANCE	=	88358.72
					=	STD. DEV.	=	313.61


UNITS OF RAW DATA VARIABLES = MM/SEC

SAMPLE SIZE = 3637 POINTS


SPANNING RANGE



FROM 69- X -06 14.53.30
TO 69- XII-04 07.53.30


DURATION 58 DAYS 17 H 0 M 0 S



AUTO SPECTRUM
3174E900 EAST COMP
3174E900 NORTH COMP
53 METERS
69-X-06 TO 69-X11-01
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS







Data number 3175

Instrument No.: M-213

Type: Magnetic tape current meter

Depth: 105 m

Water depth: 2681 m

Start time: 69-X-06 145330

Stop time: 69-XII-03 233830

Duration: 58d 8h 45m

Sampling scheme: Interval

time between strobes = 5.27 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

Digital clock - 23 seconds too fast over 3 month period.

STATS

DATA/ 3175A800

MEAN	=	EAST	NORTH	SPEED	=	*****	EAST & NORTH	*****
STD. ERR.	=	-25.25	-80.30	350.05	=	COVARIANCE	=	30040.00
VARIANCE	=	3.06	4.20	2.40	=	STD. ERR. OF COVARIANCE	=	875.00
STD. DEV.	=	52620.00	103034.11	34550.11	=	STD. DEV. OF COVARIANCE	=	85560.20
KURTOSIS	=	220.40	320.00	105.00	=	CORRELATION COEFFICIENT	=	.410
SKEWNESS	=	2.70	1.07	1.00	=	VECTOR MEAN	=	84.25
	=	-.10	-.93	.19	=	VECTOR VARIANCE	=	77030.95
					=	STD. DEV.	=	270.00

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 8004 POINTS

SPANNING RANGE


FROM 69- X -06 14.53.30


TO 69- XII-03 23.30.30

DURATION 58 DAYS 8 H 45 M 0 S




AUTO SPECTRUM
3175A900 EAST COMP
3175A900 NORTH COMP
105 METERS
69-X-06 TO 69-X11-01
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS





3175A1H
105 M
69- X -07 TO 69- XII-03



Data number 3176

Instrument No.: M-203

Type: Magnetic tape current meter

Depth: 207 m

Water depth: 2681 m

Start time: 69-X-06 145330

Stop time: 69-XII-03 173830

Duration: 58d 2h 45m 0s

Sampling scheme: Interval

time between strobes = 5.27 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

Digital clock - 15 seconds too slow over 3 month period.

STATS

DATA/ 3176000

MEAN	=	EAST	NORTH	SPEED	=	####	EAST & NORTH	####
STD. ERR.	=	-13.21	-84.43	289.02	=	COVARIANCE	=	10724.52
VARIANCE	=	2.30	3.45	1.85	=	STD. ERR. OF COVARIANCE	=	587.21
STD. DEV.	=	31668.48	66585.87	18080.24	=	STD. DEV. OF COVARIANCE	=	43664.51
KURTOSIS	=	177.86	256.06	138.06	=	CORRELATION COEFFICIENT	=	.234
SKEWNESS	=	2.30	1.82	2.01	=	VECTOR MEAN	=	65.77
	=	-.15	-.30	.24	=	VECTOR VARIANCE	=	48132.18
					=	STD. DEV.	=	221.86

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 5500 POINTS

SPANNING RANGE


FROM 69- X -06 14.53.30


TO 69- XII-03 17.38.30

DURATION 58 DAYS 2 H 45 M 0 S




AUTO SPECTRUM
3176A900 EAST COMP
3176A900 NORTH COMP
207 METERS
69-X-06 TO 69-XII-01
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS





STATION 318

9/16" NYLON



Mooring No. 318

Set 69 Oct 06 39° 19.7N 70° 02.8W
 Year Month Day Latitude Longitude

Set by J. Gifford Ship R. V. Atlantis II Cruise 53

Retrieved 70 Jan 06
 Year Month Day

Retrieved by R. Heinmiller Ship R. V. Chain Cruise 97

Purpose of Mooring: Horizontal array with station 317 and 310 at Site D.

Mooring Type: Surface mooring.

Data Number	Instrument Number	Type	Depth Meters	Comments
3181*	M-209	M.C.M.	12	
3182	M-205	M.C.M.	52	Electronic problems
3183	M-127	M.C.M.	104	Tape advance problems, also vane missing
3184	M-196	M.C.M.	206	Lost
3185	M-214	M.C.M.	1008	Lost
Water depth			2545	

COMMENTS ON MOORING:

The release did not release so the mooring was hauled. The mooring line broke below the first three current meters.

Data number 3181

Instrument No.: M-209

Type: Magnetic tape current meter

Depth: 12 m

Water depth: 2545 m

Start time: 69-X-06 182330

Stop time: 69-XII-04 015330

Duration: 58d 7h 30m

Sampling scheme: Interval

time between strobes = 5.27 seconds

no. of strobes per interval = 24

interval time = 900 seconds

COMMENTS:

Digital clock - 8 seconds too slow over 3 month period.

STATS

DATA/ 3181800

MEAN	=	EAST	NORTH	SPEED	=	####	EAST & NORTH	####
STD. ERR.	=	180.13	22.78	504.32	=	COVARIANCE	=	39862.34
VARIANCE	=	4.78	8.34	2.55	=	STD. ERR. OF COVARIANCE	=	2211.11
STD. DEV.	=	128827.28	225000.33	38357.11	=	STD. DEV. OF COVARIANCE	=	189440.55
KURTOSIS	=	355.85	474.34	188.80	=	CORRELATION COEFFICIENT	=	.201
SKEWNESS	=	1.85	1.75	2.50	=	VECTOR MEAN	=	181.75
	=	-.15	-.41	-.20	=	VECTOR VARIANCE	=	175819.00
					=	STD. DEV.	=	418.30

UNITS OF RAW DATA VARIABLES = MM/SEC


SAMPLE SIZE = 5588 POINTS

SPANNING RANGE


FROM 69- X -06 18.23.30

TO 69- XII-04 01.53.30

DURATION 58 DAYS 7 H 30 M 0 S



AUTO SPECTRUM
3181A900 EAST COMP
3181A900 NORTH COMP
12 METERS
69-X-06 TO 69-X11-02
1 PIECES WITH 2700 ESTIMATES
PER PIECE. AVERAGED OVER
8 ADJACENT FREQUENCY BANDS





N


0 100 200
KILOMETERS

3181A1H

12 M


69- X -07 TO 69- XII-04






Hydrostation Data


Number	Latitude	Longitude	Page
CI-92-896	39° 07.0'N	70° 00.0'W	112
CI-92-898	39° 02.3'N	70° 02.8'W	114
CI-92-903	39° 09.4'N	70° 06.5'W	116
CI-95-922	39° 10.5'N	70° 01.2'W	118
CI-95-924	34° 01.0'N	70° 04.7'W	120
AN-53-1550	39° 09.0'N	70° 03.0'W	122
AN-53-1551	39° 59.0'N	70° 02.0'W	124
AN-53-1552	39° 12.5'N	70° 05.0'W	126




CI - 092 - 896




CI-092-898




CI-092-903




CI - 095 - 922




CI-095-924



AN - 053 - 1550



AN - 053 - 1551



AN - 053 - 1552

References

- Berteaux, H. O., and R. Heinmiller, 1969
Back-up recovery systems of deep-sea moorings. W.H.O.I. Ref. 69-7
(unpublished manuscript).
- Chausse, D., and S. Tarbell, 1974
A compilation of moored current meter and wind observations, Volume VII
(1968 measurements). W.H.O.I. Ref. 74-52 (unpublished manuscript).
- Maltais, J. A., 1969
A nine channel digital magnetic tape format for storing oceanographic
data. W.H.O.I. Ref. 69-55 (unpublished manuscript).
- Pollard, R. T., 1970
A compilation of moored wind and current meter observations. W.H.O.I.
Ref. 70-40 (unpublished manuscript).
- Pollard, R. T., and S. Tarbell, 1975
A compilation of moored current meter and wind observations, Volume VIII
(1970 Array experiment). W.H.O.I. Ref. 75-7 (unpublished manuscript).
- Singleton, R. C., 1969
An algorithm for computing the mixed radix Fast Fourier Transform.
I.E.E.E. Trans. on Audio and Electroacoustics, AU-17 (2) 93-103.
- Tarbell, S., 1974
A compilation of moored wind and current observations taken in
1967. W.H.O.I. Ref. 74-7 (unpublished manuscript).
- Tarbell, S., 1976
A compilation of moored current data and associated oceanographic
observations, Volume X (Early 1969 measurements). W.H.O.I. Ref. 76-40
(unpublished manuscript).
- Tarbell, S., M. G. Briscoe, and D. Chausse, 1976
A compilation of moored current data and associated oceanographic
observations, Volume IX (1973 Internal Wave Experiment (IWEX)).
W.H.O.I. Ref. 75-68 (unpublished manuscript).
- Tarbell, S., and F. Webster, 1971
A compilation of moored current meter and wind observations, Volume V
(1966 measurements). W.H.O.I. Ref. 71-50 (unpublished manuscript).
- Volkman, G. H., 1970
Mooring summary 1967. W.H.O.I. Ref. 70-37 (unpublished manuscript).

References (cont.)

Webster, F., and N. P. Fofonoff, 1965

A compilation of moored current meter observations, Volume I.
W.H.O.I. Ref. 65-44 (unpublished manuscript).

Webster, F., and N. P. Fofonoff, 1966

A compilation of moored current meter observations, Volume II.
W.H.O.I. Ref. 66-60 (unpublished manuscript).

Webster, F., and N. P. Fofonoff, 1967

A compilation of moored current meter observations, Volume III.
W.H.O.I. ref. 67-66 (unpublished manuscript).

MANDATORY DISTRIBUTION LIST

**FOR UNCLASSIFIED TECHNICAL REPORTS, REPRINTS, & FINAL REPORTS
PUBLISHED BY OCEANOGRAPHIC CONTRACTORS
OF THE OCEAN SCIENCE AND TECHNOLOGY DIVISION
OF THE OFFICE OF NAVAL RESEARCH
(REVISED OCT. 1975)**

- | | |
|--|--|
| <p>1 Director of Defense Research
 and Engineering
 Office of the Secretary of Defense
 Washington, DC 20301
 ATTN: Office Assistant Director
 (Research)</p> <p> Office of Naval Research
 Arlington, VA 22217</p> <p>3 ATTN: (Code 480)
1 ATTN: (Code 460)
1 ATTN: (Code 102-OS)
6 ATTN: (Code 102IP)
1 ATTN: (Code 200)</p> <p>1 LCDR David Cacchione, (USN)
 ONR Representative
 Woods Hole Oceanographic Inst.
 Woods Hole, MA 02543</p> <p>1 Office of Naval Research
 Branch Office
 495 Summer Street
 Boston, MA 02210</p> <p> Director
 Naval Research Laboratory
 Washington, DC 20375</p> <p>6 ATTN: Library, Code 2620</p> <p>1 National Oceanographic Data Center
 National Oceanic & Atmospheric
 Administration
 Rockville, MD 20852</p> | <p>12 Defense Documentation
 Center
 Cameron Station
 Alexandria, VA 22314</p> <p> Commander
 Naval Oceanographic
 Office
 Washington, DC 20390</p> <p>1 ATTN: Code 1640
1 ATTN: Code 70</p> |
|--|--|

<p>Woods Hole Oceanographic Institution WHOI-76-41</p> <p>A COMPILATION OF MOORED CURRENT DATA AND ASSOCIATED OCEANOGRAPHIC OBSERVATIONS, VOLUME XI (LATE 1969 MEASUREMENTS) by Susan A. Tarbell. 150 pages. Prepared under ONR Contracts N00014-66-C-0241; NR 083-004 and N00014-76-C-0197; NR 083-400.</p> <p>Summaries of wind and current measurements from moored stations gathered by magnetic tape recording current meters and wind recorders, in late 1969 are presented also selected hydrostation data from the same areas.</p> <p>Averaged wind and current quantities are presented in computer generated output as basic STATISTICS, SPECTRA diagrams, PROGRESSIVE VECTOR diagrams and EAST-NORTH component plots. The hydrostation data are presented as temperature and salinity values plotted against pressure.</p>	<p>1. Site D</p> <p>2. Current Date</p> <p>3. Moorings</p> <p>I. Tarbell, Susan A.</p> <p>II. N00014-66-C-0241; NR 083-004</p> <p>III. N00014-76-C-0197; NR 083-400</p> <p>This card is UNCLASSIFIED</p>	<p>Woods Hole Oceanographic Institution WHOI-76-41</p> <p>A COMPILATION OF MOORED CURRENT DATA AND ASSOCIATED OCEANOGRAPHIC OBSERVATIONS, VOLUME XI (LATE 1969 MEASUREMENTS) by Susan A. Tarbell. 150 pages. Prepared under ONR Contracts N00014-66-C-0241; NR 083-004 and N00014-76-C-0197; NR 083-400.</p> <p>Summaries of wind and current measurements from moored stations gathered by magnetic tape recording current meters and wind recorders, in late 1969 are presented also selected hydrostation data from the same areas.</p> <p>Averaged wind and current quantities are presented in computer generated output as basic STATISTICS, SPECTRA diagrams, PROGRESSIVE VECTOR diagrams and EAST-NORTH component plots. The hydrostation data are presented as temperature and salinity values plotted against pressure.</p>	<p>1. Site D</p> <p>2. Current Date</p> <p>3. Moorings</p> <p>I. Tarbell, Susan A.</p> <p>II. N00014-66-C-0241; NR 083-004</p> <p>III. N00014-76-C-0197; NR 083-400</p> <p>This card is UNCLASSIFIED</p>
<p>Woods Hole Oceanographic Institution WHOI-76-41</p> <p>A COMPILATION OF MOORED CURRENT DATA AND ASSOCIATED OCEANOGRAPHIC OBSERVATIONS, VOLUME XI (LATE 1969 MEASUREMENTS) by Susan A. Tarbell. 150 pages. Prepared under ONR Contracts N00014-66-C-0241; NR 083-004 and N00014-76-C-0197; NR 083-400.</p> <p>Summaries of wind and current measurements from moored stations gathered by magnetic tape recording current meters and wind recorders, in late 1969 are presented also selected hydrostation data from the same areas.</p> <p>Averaged wind and current quantities are presented in computer generated output as basic STATISTICS, SPECTRA diagrams, PROGRESSIVE VECTOR diagrams and EAST-NORTH component plots. The hydrostation data are presented as temperature and salinity values plotted against pressure.</p>	<p>1. Site D</p> <p>2. Current Date</p> <p>3. Moorings</p> <p>I. Tarbell, Susan A.</p> <p>II. N00014-66-C-0241; NR 083-004</p> <p>III. N00014-76-C-0197; NR 083-400</p> <p>This card is UNCLASSIFIED</p>	<p>Woods Hole Oceanographic Institution WHOI-76-41</p> <p>A COMPILATION OF MOORED CURRENT DATA AND ASSOCIATED OCEANOGRAPHIC OBSERVATIONS, VOLUME XI (LATE 1969 MEASUREMENTS) by Susan A. Tarbell. 150 pages. Prepared under ONR Contracts N00014-66-C-0241; NR 083-004 and N00014-76-C-0197; NR 083-400.</p> <p>Summaries of wind and current measurements from moored stations gathered by magnetic tape recording current meters and wind recorders, in late 1969 are presented also selected hydrostation data from the same areas.</p> <p>Averaged wind and current quantities are presented in computer generated output as basic STATISTICS, SPECTRA diagrams, PROGRESSIVE VECTOR diagrams and EAST-NORTH component plots. The hydrostation data are presented as temperature and salinity values plotted against pressure.</p>	<p>1. Site D</p> <p>2. Current Date</p> <p>3. Moorings</p> <p>I. Tarbell, Susan A.</p> <p>II. N00014-66-C-0241; NR 083-004</p> <p>III. N00014-76-C-0197; NR 083-400</p> <p>This card is UNCLASSIFIED</p>